

		Tires		Clutch settings		Front shocks		Engine	
		Front shore	left 37 / right 37	Shoe/Bell	STD / T2722	Piston	1 X 1.1	Type	
Date/Track	VILA REAL	Rear shore	left 40 / right 40	Bell clearance (mm)	0.5	Oil	450	Plug/Fuel	Plug / Fuel
Driver	THOMAS ANDRADE	Front ϕ	left 60 / right 60	Spring/adj. Nut(mm)	H2710 /	Spring	T2507	Pipe/Manifold	Pipe / Manifold
Temp. °C.	air / track	Rear ϕ	left 62 / right 62	Bell axial play (mm)	0.2	Rear shocks		Gear ratio chart	
Track layout/traction	technical <input type="radio"/> low <input type="radio"/>	Differential		Gearing		Piston	2 X 1.1	Spur Pinion	1st 52 53 54 47 48 49
	mixed <input type="radio"/> medium <input type="radio"/>	Front diff. oil cst.	500.000	1st gear	15 / 52	Oil	550	1st	14 7,614 7,761 7,907 15 7,107 7,243 7,38
	fast <input checked="" type="radio"/> high <input type="radio"/>	Rear diff. oil cst.	60.000	2n gear	20 / 48	Spring	H0528	2nd	19 5,071 5,179 5,278 20 4,818 4,92 5,023 21 4,588 4,686 4,783

